

FEATURES

Premium Aesthetic Appeal

Grafika Fine Print is a high bright paper with 88% ISO brightness for exceptional visual appearance.

Superior Strength

Its high tensile strength properties ensure suitability for sublimation process and durability in diverse printing operations.

Suitable for High-speed Printing Machines

Its excellent breaking length enhances productivity on high-speed printing machines.

Superior Ink Absorption

Designed to absorb ink efficiently, resulting in rich, vibrant colours and sharp text for visually striking print results.

Enhanced Longevity

Crafted to resist fading and yellowing, preserving the integrity and appearance of printed materials over extended periods.

Tested and approved for FSC

Complies with FSC (Forest Stewardship Council) chain of custody certification (TAH-COC-009416).

Certification



Application

Notebooks & Publications

Stationery & Flyers

Receipt Book

Sublimation Printing for Textile



Grafika Fine Print (GFP)



Product Specification

Parameter		Specification					Unit	Method	Tolerance
GSM	-	48	50	52	54	56	gm/m ²	TAPPI T 410 om-98	±2.5%
Bulk	-	140	140	140	140	140	cc/gm		±0.03
COBB₆₀	Top	25					gm/m ²	TAPPI T 441 om-98	Max
Brightness	Top	88					% ISO	TAPPI T 452 om-98	±1.0
Opacity	-	90.0	91.0	91.0	93.0	93.0	%	TAPPI T 519 om-96	Min
Wax Pick	-	12-A					no.	TAPPI T 459 om-93	Min
Breaking Length	MD	4800	5000	5000	5200	5200	mtr	TAPPI T 404 cm-92	±200
	CD	2200	2200	2200	2200	2200	mtr	TAPPI T 404 cm-92	±200
Tear Factor	MD	55					-	TAPPI T 414 om-98	Min
	CD	65					-	TAPPI T 414 om-98	Min
Bendtsen Smoothness	Top	130	130	130	130	130	ml/min	ISO 8791-2	Min
		160	160	160	160	160	ml/min	ISO 8791-2	Max
	Bottom	140	140	140	140	140	ml/min	ISO 8791-2	Min
		180	180	180	180	180	ml/min	ISO 8791-2	Max

Deckle

Machine 5

Min.- 640 cm | Max.- 645 cm

Machine Suitability

Recommended for High-speed printing machines with text and illustration work.

Packaging Information

PALLETS

Min. Height: 1100 mm
Max. Height: 1300 mm

SHEETS

Min. Size: 390 x 510 mm
Max. Size: 900 x 1350 mm

REELS

Width: 230-2200 mm
Core Inner Dia: 76 mm/3"