



## FEATURES

### Enhanced Visual Appeal

Grafika Lite Paper provides clear, vibrant prints with 88% ISO brightness for outstanding visual clarity and appearance.

### Enhanced Strength, Lightweight Build

Despite its lower bulk, GLP offers exceptional strength, high formation and dimensional stability, making it perfect for lightweight yet durable print applications.

### Designed for Speed and Productivity

GLP delivers exceptional ink absorption and smudge free performance, ensuring quality and efficiency in high-speed printing applications.

### Smooth Surface

The uniform and refined surface guarantees precise and vivid prints, providing vibrant colour reproduction with exceptional results for professional grade materials.

### Cost-Effective Performance

Combining premium quality with affordability, GLP is the ideal choice for large-scale printing projects, delivering exceptional value without compromising on performance.

### Tested and approved for FSC

Complies with FSC (Forest Stewardship Council) chain of custody certification (TAH-COC-009416).

## Certification



## Application

Notebooks & Publications

Office Stationery

Calendar Printing

Diaries



## Product Specification

Parameter		Specification					Unit	Method	Tolerance
<b>GSM</b>	-	48	50	52	54	56	gm/m <sup>2</sup>	TAPPI T 410 om-98	±2.5%
<b>Bulk</b>	-	1.30	1.30	1.30	1.30	1.30	cc/gm		±0.03
<b>COBB<sub>60</sub></b>	Top	25					gm/m <sup>2</sup>	TAPPI T 441 om-98	Max
<b>Brightness</b>	Top	88					% ISO	TAPPI T 452 om-98	±1.0
<b>Opacity</b>	-	90.0	90.0	91.0	93.0	93.0	%	TAPPI T 519 om-96	Min
<b>Wax Pick</b>	-	12-A					no.	TAPPI T 459 om-93	Min
<b>Breaking Length</b>	MD	4800	5000	5000	5200	5200	mtr	TAPPI T 404 cm-92	±200
	CD	2200	2200	2200	2200	2200	mtr	TAPPI T 404 cm-92	±200
<b>Tear Factor</b>	MD	55					-	TAPPI T 414 om-98	Min
	CD	60					-	TAPPI T 414 om-98	Min
<b>Bendtsen Smoothness</b>	Top	130	130	130	130	130	ml/min	ISO 8791-2	Min
		160	160	160	160	160	ml/min	ISO 8791-2	Max
	Bottom	140	140	140	140	140	ml/min	ISO 8791-2	Min
		180	180	180	180	180	ml/min	ISO 8791-2	Max

### Deckle

#### Machine 5

Min.- 640 cm | Max.- 645 cm

### Machine Suitability

Recommended for High-speed printing machines with text and illustration work.

### Packaging Information

#### PALLETS

Min. Height: 1100 mm  
Max. Height: 1300 mm

#### SHEETS

Min. Size: 390 x 510 mm  
Max. Size: 900 x 1350 mm

#### REELS

Width: 230-2200 mm  
Core Inner Dia: 76 mm/3"